

Specification YS_v20

YARDMASTER® INCLINED SCREW SEPARATOR

- The Yardmaster screw separator is designed to separate solids out of liquid
- Reduces bad odours, settlement in the lines
- Cleaner systems
- Can use separated water for wash down
- No blockages at irrigator
- More efficient pumping
- Reuse solids for fertiliser
- Designed and manufactured in New Zealand for New Zealand conditions



Ideal for...

Dairy farms, paper mills, food industry, abattoirs, wineries, piggeries and poultry and waste water treatment

Technical Specifications

Model	Screen Size (mm)	Screen Type	Capacity (m ³ /hr) <10% solids loading	Motor Size (kW)	Weight (approx kg)	Dimensions (WxDxH mm)
YS200C	2 ^s ,3,4	Perforated Mesh	Up to 25*	2.2	375	1380x1800x1580
YS200	2 ^s ,3,4	Perforated Mesh	Up to 30	3	620	1400x4250x3140
YS300	2 ^s ,3,4	Perforated Mesh	Up to 40	4	835	1800x4000x3300

* Grass fed only, ^s Stainless steel

Specifications are subject to change without notice

Applications & Case Studies



CS_CRA01
YS300 separator

CS_HED01
YS200mini separator

CS_BEN01
YS300 separator, transferring into spreading wagon

CS_SCA01
YS200 separator